

May 21, 2020

RFB 2005- S-159 UPPER AND MIDDLE CONCRETE RESTORATION PROJECT IN HILLSBOROUGH COUNTY, FLORIDA

ADDENDUM #3 (Acknowledgment is Required)

The Respondent must acknowledge the receipt of this Addendum by signing below and including a signed copy of this Addendum with its Request for Proposal.

Please note that underlined information (<u>example</u>) is added wording and stricken information (<u>example</u>) is deleted wording.

Please note the following change to the third paragraph of **Section 3.6**, **EPOXY CRACK REPAIR**, of the above referenced solicitation:

3.6 **EPOXY CRACK REPAIR.** Epoxy shall be injected into all cracks in damaged concrete as indicated by the District in those walls included in the Scope of Work listed herein. Installation instructions and recommendations by the epoxy manufacturer shall be followed.

Cracks shall be injected with sufficient pressure to ensure full penetration of the epoxy but without causing further damage.

The location, drilling, and preparation of ports for injection shall be as required for chemical grout <u>Epoxy</u> <u>Injection</u> herein.

Brian Bickhardt Senior Procurement Specialist cc: Project Manager

ACKNOWLEDGEMENT OF ADDENDUM #3

BY: _____

DATE

(TYPE/PRINT NAME AND TITLE)

COMPANY NAME